

4'0" x 7'0" Welded Steel In-Stock Quick Ship Booth

This one is Built & Ready to Ship in 2-4 Weeks!

GENERAL SITE INSTALLED ITEMS PROVIDED BY OTHERS

- 1 PROVIDE 120V/240V, SINGLE PHASE, 3-WIRE SERVICE WITH-GROUND.
- 2 CONCRETE FOUNDATION MINIMUM 6" DEEP, 3,000 PSI MINIMUM (28 DAY ACI 318). THE FOUNDATION SHOULD BE A MINIMUM OF 2" WIDER THAN THE BUILDING FOOT PRINT DIMENSIONS. THIS IS TO PROVIDE A 1" CONCRETE BORDER ON EACH SIDE OF THE BUILDING.
- 3 ADEQUATE SIZE DRILLED ANCHOR BOLTS, SUGGESTED SIZE: 3/4" X 48" POWER FASTENERS "POWER STOP" CATALOG #7331.

SERVICE ENTRANCE / ANCHOR BOLT LAYOUT

ITEM	DESCRIPTION	QTY.
1	3" X 4" SLOT IN FLOOR WITH 3" X 8" REMOVABLE SCREWDOWN ALUMINUM TREADPLATE LTD. (2) SCREWS PERIOD ONE AT EACH END, FOR ELECTRICAL SERVICE ENTRANCE TO C.B. PANEL.	1
2	2" X 2" X 3/16" THIN STEEL ANCHOR CLIP WITH A 3/4" ANCHOR BOLT-HOLE, ONE EACH CORNER ANCHOR BUILDING AFTER FINAL LOCATION ANCHOR BOLTS NOT INCLUDED	4
3	OUTER EDGE OF BUILDING	1
4	BASE PERIMETER FRAME	1
5	INTERIOR WALL FACE	1
6	SUGGESTED MINIMUM FOUNDATION	1

GENERAL CONSTRUCTION NOTES

PAR-KUT BOOTHS ARE OF SINGLE UNIT WELDED STEEL CONSTRUCTION, FACTORY ASSEMBLED AND DELIVERED SET UP. FAILURE TO SECURELY ANCHOR BOOTH MAY RESULT IN OVERTURNING OF UNIT AND SERIOUS INJURY TO OCCUR.

GLAZING - CLEAR TEMPERED SAFETY GLAZING SET IN PAINTED GALVANIZED STEEL EXTERIOR WINDOW FRAMES WITH INTERIOR ALUMINUM GLAZING STOPS.

PAINT - FINISH SHALL BE SINGLE COLOR OF CHOICE UNLESS OTHERWISE SPECIFIED. AVALA THIN POLYURETHANE INDUSTRIAL COATING SHALL BE APPLIED TO ALL EXPOSED METAL SURFACES. THIS EXCLUDES ROOF SURFACE, ALUMINUM WINDOW COATINGS AND ANY STAINLESS STEEL COMPONENTS (IF USED).

ELECTRICAL - ALL WIRING BY PAR-KUT TO BE #12/1000 STRANDED COPPER, TRAIL ENCLOSED IN NYLON EMT AND FLEXIBLE PIPING CORRECT WIRING APPLICABLE PER NATIONAL ELECTRICAL CODE. ALL ELECTRICAL EQUIPMENT WILL BE LISTED BY UL OR EQUIVALENT RECOGNIZED NATIONAL TESTING LABORATORY. ALL WIRING TO TERMINATE AT C.B. PANEL. ALL CIRCUITS HAVE GREEN GROUND WIRE.

BOOTH WILL HAVE A 3" CANOPY OVERHANG ON ALL SIDES.

REMOVABLE LIFTING RINGS ARE PROVIDED ON ROOF.

LIFTING RINGS ARE DESIGNED FOR A STRAIGHT VERTICAL LIFT ONLY. SPREADER BARS MUST BE USED WHERE APPLICABLE TO ENLARGE STRAIGHT VERTICAL LIFT. ALL WARRANTIES WILL BE VOID IF NOT LISTED IN THIS MANUAL.

NO ON SITE WORK BY PAR-KUT.

ACTUAL LOCATION OF ELECTRICAL DEVICES MAY VARY DUE TO INSTALLATION CONSTRAINTS, SHIPPING RESTRICTIONS, OR FOR PROPER PLACEMENT TO SATISFY APPLICABLE CODES.

FLOOR PLAN MAY BE MODIFIED OR NOTIFIED UPON CUSTOMER REQUEST.

LINE ITEMS

ITEM #	DESCRIPTION	QTY.
1	COUNTER - 28" DEEP PAINTED GALVANIZED STEEL MOUNTED 22" A.F.F.	1
2	PAINTED STORAGE DRAWER.	1
3	DOOR - 36" SLIDING STEEL WITH WEATHERSTRIKING WALL BEARING HANGERS, HEAVY DUTY TRACK, SAFETY GLAZING, HOOK BOLT LOCK AND HARDWARE.	1
4	2" DIAMETER HOLE IN COUNTER FOR DROP CORDS.	1
5	DUPLEX OUTLET MOUNTED BELOW COUNTER.	1
6	EXTERIOR LIGHT WITH WALL SWITCH - 24" LED LIGHT FIXTURE WITH ACRYLIC LENS.	1
7	WALL SWITCH FOR INTERIOR LIGHT.	1
8	DUPLEX OUTLET MOUNTED 28" A.F.F.	1
9	HVAC UNIT - HEAT EXCH. COMBO 1,000 BTU THROUGH WALL MOUNTED WITH WINDSHIELD REMOTE CONTROL.	1
10	SINGLE RECEPTACLE FOR HVAC UNIT.	1
11	CIRCUIT BREAKER PANEL - 120/240V RATED [CAN BE FED WITH 120/208V], 12 SPACE, 100% WIRE WITH GROUNDING BUS, 300 AMP MAIN BREAKER AND BRANCH BREAKERS FOR FACTORY INSTALLED DEVICES PROVIDED.	1

GENERAL NOTES & COLORS

HIGH GLOSS FINISH PAINT COLOR: _____

SHIPPING NOTES

OVERALL SHIPPING DIMENSIONS: 2'-0" X 11'-0" X 8'-0" A
 ESTIMATED WEIGHT: 2,000 LBS. E

SOME ITEMS MAY BE SHIPPED LOOSE TO MEET SHIPPING CONSTRAINTS. DRAIN DOWNSPOUTS ARE SHIPPED LOOSE AND INSTALLED ON SITE BY OTHERS.

GENERAL NOTES & COLORS

NOTE: THIS PRINT AND ORDER SEE THE PROPERTY OF PAR-KUT INTERNATIONAL, INC. IT MUST NOT BE REPRODUCED IN ANY MANNER, FOR SALE OR DISTRIBUTION WITHOUT OUR CONSENT. IT SHALL BE VOID ONLY AS A BASIS OF VERIFICATION OF WORK PROVIDED AND FURNISHED BY PAR-KUT. PAR-KUT RESERVES THE RIGHT TO MAKE CHANGES TO ORDER FOR UNFORSEEN REASONS WITHOUT NOTICE. 2-21-1988 22-198 22-198 22-198

PAR-KUT INTERNATIONAL, INC.
 40961 Production Drive
 Harrison Twp., MI, 48045
 (586) 468-2947
 www.parkut.com

DATE: 22-198 SHEET: A-1

STOCK

4' x 7' insulated steel booth to be sold on a first come, first serve basis includes: - 36" Wide Top Hung Sliding Steel Door w/window & hook bolt Lock - 7'6" floor to ceiling height, Clear tempered glass Windows in All Sides for Excellent Visibility, Factory Wired thru wall HVAC unit, factory installed light, two duplex outlets and breaker panel, Built in Counter-Top w/Drawer, Treadplate Steel Floor, 3" Canopy Roof, DrainPipe - Finish Paint Standard White or Choice of Single Standard Color

\$11,911.00 + Freight
(Add Sales Tax if Applicable)

****Minor Modifications May be Available. (ie. Ext. lights, more outlets)****